

TurfRx C-85

INCREASES MICROBIAL DIVERSITY



GUARANTEED ANALYSIS

Available Phosphate (P_2O_5)..... 1%
Soluble Potash (K_2O) 6%
ALSO CONTAINS NON-PLANT FOOD INGREDIENTS
Humic Acid..... 8%

WHY **TurfRx** C-85 ?

TurfRx C-85 is a multi-extraction humic and fulvic acid that contains short-, medium-, and long-chain soluble carbon molecules.

MICROBIAL DIVERSITY

TurfRx C-85 is soluble across a broad pH range, improving soluble carbon availability in all soil types. The availability of soluble carbon across a broad pH range increases soil microbial diversity and soil health.

NITROGEN EFFICIENCY

When combined with synthetic nitrogen, **TurfRx C-85** will increase nitrogen efficiency by at least 25%.

PRODUCT USAGE

Soil Health	Apply 0.5-2 gal/acre (0.75-3 oz./1000 ft ²) as a soil application every 1 to 3 weeks throughout the growing season. Water in.
Water Retention	Apply 0.5-2 l gal/acre (0.75-3 oz./1000 ft ²) as a soil application every 1 to 3 weeks throughout the growing season. Water in.
Thatch Reduction	Apply 0.5-2 l gal/acre (0.75-3 oz./1000 ft ²) as a soil application every 1 to 3 weeks throughout the growing season. Water in.
Nitrogen Efficiency	Apply 0.5-2 l gal/acre (0.75-3 oz./1000 ft ²) as a soil application every 1 to 3 weeks throughout the growing season. Water in.

TurfRx C-85

TurfRx C-85 HANDLING GUIDELINES

PRE-MIXING

Pre-mixing is considered a best practice when sprayer agitation is not optimum. Proper hydration is essential for all applications. Recirculate or agitate while adding material.

ONCE THE MATERIAL IS ADDED TO WATER, CONSTANT AGITATION IS REQUIRED.

COMPATABILITY

Always jar test first.

Redox products are compatible with other Redox products when following product handling guidelines.

Use caution with reactive materials.

Avoid extreme shifts in tank pH. When utilizing Redox materials that acidify, check tank pH prior to adding buffers.

TANK MIXING

Use of an anti-foaming agent is recommended. Fill the tank 50% full with water and initiate tank agitation prior to adding materials.

Don't add material too quickly—this allows for more thorough hydration.

The use of inductor assemblies is encouraged.

Recirculate or agitate while adding material.

If material is not applied immediately, tank recirculation is required prior to application to ensure uniform product distribution.

ONCE THE MATERIAL IS ADDED TO WATER, CONSTANT AGITATION IS REQUIRED.

REFER TO PRODUCT HANDLING GUIDELINES FOR ADDITIONAL MIXING INSTRUCTIONS.
